

The Platform for the Perfect Meeting – Anytime, Anywhere

AMX welcomes you to Enova DVX, the platform for the perfect meeting in any room configuration from small to large, simple to complex!

ENDLESSLY ENOVATIVE

Enova DVX All-In-One Presentation Switchers dramatically simplify AV distribution and control in small to large conference rooms, classrooms and auditoriums and are ideal for any room with a mix of analog and digital sources, multiple displays, or rooms that need support for video conferencing. The DVX family includes exclusive technologies like SmartScale and InstaGate Pro that ensure that all your displayed content looks perfect from the start, with no hassles, regardless of its source.



PERFECTLY SIMPLE, SIMPLY PERFECT

AMX has built reliability and dependability into the Enova DVX by integrating a variety of AV capabilities into a single chassis, thereby eliminating unruly cabling and points of failure. The DVX combines AV switching, control, audio processing, amplification and category cable distribution in a single chassis roughly the size of a desktop PC that can be supported and serviced remotely over your current IT infrastructure.



YES, WE HAVE A DVX FOR THAT

The Enova DVX family begins with the DVX-2150HD and 2155HD, which are ideal for small to medium-sized installations. These 6X3 switchers include scaled HDMI outputs and provide ample horsepower for a typical commercial conference room. The largest of the DVX family, the DVX-3150HD and 3155HD, are 10X4

switchers that can handle the most complex AV requirements in venues such as boardrooms and auditoriums.

WHY ENOVA SETS THE STANDARD

The Enova DVX offers a long list of valuable capabilities:

- Standardize on the Enova DVX platform for a consistent, hassle-free meeting experience in every room.
- Easy to use, maintain and troubleshoot.
- Small footprint in single chassis delivers lowest cost of ownership and highest reliability.
- Save energy costs with AMX's intelligent energy utilization.
- Intuitive and effective monitoring and setup with AMX's Resource Management Suite and Rapid Project Maker Software.

The bottom line is that the Enova DVX is unquestionably the most versatile family of presentation switchers on the market today. Visit amx.com to learn more.

All-In-One Presentation Switchers

6x3s

Includes 2 independent, scaled HDMI outputs and 1 unscaled DXLink output with power

DVX-2150HD-SP

6 Video Inputs (2 Multi-Format DVI (HDMI/HDCP capable), 4 HDMI/HDCP), 2x25w - 8 Ohm amplifier



DVX-2150HD-SP

DVX-2150HD-T

6 Video Inputs (2 Multi-Format DVI (HDMI/HDCP capable), 4 HDMI/HDCP), 75w - 70V/100V amplifier



DVX-2150HD-T

DVX-2155HD-SP

6 Video Inputs (2 Multi-Format DVI (HDMI/HDCP capable), 2 HDMI/HDCP, 2 DXLink), 2x25w - 8 Ohm amplifier



DVX-2155HD-SP

DVX-2155HD-T

6 Video Inputs (2 Multi-Format DVI (HDMI/HDCP capable), 2 HDMI/HDCP, 2 DXLink), 75w - 70V/100V amplifier



DVX-2155HD-T

10x4s

Includes 4 independent scaled HDMI outputs and 2 DXLink outputs (unpowered) that mirror two of the scaled HDMI outputs

DVX-3150HD-SP

10 Video Inputs (4 Multi-Format DVI (HDMI/HDCP capable), 6 HDMI/HDCP), 2x25w - 8 Ohm amplifier



DVX-3150HD-SP

DVX-3150HD-T

10 Video Inputs (4 Multi-Format DVI (HDMI/HDCP capable), 6 HDMI/HDCP), 75w - 70V/100V amplifier



DVX-3150HD-T

DVX-3155HD-SP

10 Video Inputs (4 Multi-Format DVI (HDMI/HDCP capable), 4 HDMI/HDCP, 2 DXLink), 2x25w - 8 Ohm amplifier



DVX-3155HD-SP

DVX-3155HD-T

10 Video Inputs (4 Multi-Format DVI (HDMI/HDCP capable), 4 HDMI/HDCP, 2 DXLink), 75w - 70V/100V amplifier



DVX-3155HD-T

Switcher	Model	Amplifier	Multi-Format Inputs	HDMI Inputs	DXLink Inputs	Analog Audio Inputs	HDMI Outputs	DXLink Outputs	Analog Audio Outputs	Control Ports (Serial/IR/IO/Relay)
6x3	DVX-2150HD-SP	2x25w - 8 Ohm	2	4	0	4	2	1*	3	3/4/4/4
	DVX-2150HD-T	75w -70V/100V	2	4	0	4	2	1*	3	3/4/4/4
	DVX-2155HD-SP	2x25w - 8 Ohm	2	2	2	4	2	1*	3	3/4/4/4
	DVX-2155HD-T	75w -70V/100V	2	2	2	4	2	1*	3	3/4/4/4
10x4	DVX-3150HD-SP	2x25w - 8 Ohm	4	6	0	8	4	2**	4	6/8/8/8
	DVX-3150HD-T	75w -70V/100V	4	6	0	8	4	2**	4	6/8/8/8
	DVX-3155HD-SP	2x25w - 8 Ohm	4	4	2	8	4	2**	4	6/8/8/8
	DVX-3155HD-T	75w -70V/100V	4	4	2	8	4	2**	4	6/8/8/8

Switcher	Model	Amplifier	Multi-Format Inputs	UDM Inputs	Analog Audio Inputs	Video Outputs	UDM Outputs	Analog Audio Outputs	Control Ports (Serial/IR/IO/Relay)
6x2	DVX-2100HD-SP/T***	2x25w - 8 Ohm	4	2	4	2	1	2	3/4/4/4

* DVX-215x DXLink output is an independent, unscaled output with power. Scaling occurs at DXLink Receiver.

** DVX-315x DXLink outputs are unpowered, paired with an HDMI output & contain identical audio & video content & resolution as companion HDMI output.

*** DVX-2100HD-T model includes 75w - 70V/100V amplifier.

enova DVX